

FoxSec Touch 10.1" PoE

10pt touch screen with Android and Power over Ethernet Technology. FoxSec Touch is a perfect choice for your facility.

DISPLAY CHARACTERISTICS

Diagonal
Panel
Native resolution
Aspect ratio
Panel brightness
Brightness
Light transmittance
Static contrast
Response time
Viewing zone

Colour support Viewable area Pixel pitch Bezel colour and finish

INTERFACES / CONNECTORS / CONTROLS Digital signal output

Digital signal output Audio output USB ports RJ45 (LAN)

INTERFACES

Digital signal output Audio output USB ports RJ45 (LAN)

FEATURES

Integrated software

POWER MANAGEMENT

Power supply unit Power supply Power usage

SUSTAINABILITY

Regulations REACH SVHC

DIMENSIONS / WEIGHT

Product dimensions

10.1", 25.5cm
IPS Panel Technology, LED
1280 x 800 (1 megapixel HD)
16:10
450 cd/m²
385 cd/m² with touch
85%
1000:1 with touch
(GTG) 25ms
horizontal/vertical: 160°/160°, right/left:
80°/80°, up/down: 80°/80°
16.7mln 8bit
W x H 216.6 x 135.4mm, 8.5 x 5.3"
0.1692mm

HDMI x1 (mini HDMI, 1280x720 @60Hz) Speakers 2 x 1.5W x2 (2.0, 1 x MICRO with OTG) x1 (PoE

HDMI x1 (mini HDMI, 1280x720 @60Hz) Speakers 2 x 1.5W x2 (2.0, 1 x MICRO with OTG) x1 (PoE)

Android 8.1 without GMS

external (included) DC 12 V 7W typical

black, matte

CE, RoHS support, ErP, WEEE, REACH above 0.1%: Lead

W x H x D 255 x 172 x 3



